4.8 Coach



DESIGNED BY COACHES, FOR COACHES.



The RIBCRAFT 4.8 Coach delivers professional grade performance, reliability and durability that have become synonymous with the RIBCRAFT line of RIBs.

The commercial grade construction combined with functional simplicity make the 4.8 Coach the ideal safety boat for sailing programs and yacht clubs. A proven RIB designed and built for the sailing community, the 4.8 Coach offers a forward position console for improved visibility, open deck for marks, sailors and gear, and a deep V hull for unmatched performance while underway. RIBCRAFT has worked with coaches and programs to develop the only boat designed specifically for coaching.

4.8 COACH SPECS

LOA:	15'7"	INTERNAL LENGTH ON DECK:	11'10"
BEAM:	6'11"	INTERNAL BEAM ON DECK:	4'1"
WEIGHT (W/OUT ENGINE):	685 LBS	DRAFT (W/OUT ENGINE):	12"
DEAD RISE AFT:	23°	MAXIMUM PEOPLE:	6
DEAD RISE FORWARD:	43°	MAX HP:	70
TUBE DIAMETER:	18"		

4.8 COACH STANDARD EQUIPMENT:

- Single seat console with attached pod seat and upholstered backrest
- Stainless steel console grab rail
- Heavy duty no feedback steering with wheel
- 1670 dtx Hypalon® tube with 5 chambers and pressure relief valves
- External lifelines
- · Heavy duty rubstrake
- Stainless steel bow eye
- Anchor locker
- · Stainless steel bow cleat
- Stainless steel lifting points
- Stainless steel transom tie down eyes
- · Battery with retainer
- Electric bilge pump
- · Underdeck wire conduit
- Molded non-skid deck

4.8 COACH OPTIONAL EQUIPMENT: (PARTIAL LIST)

- Additional pod seat with upholstered backrest and grab handle
- Two person bench seat with storage
- Aft tow post
- Transom bollards
- Folding bimini
- Boarding wear patches
- Tube grab handles
- Paddle/hook retainers
- Custom Hypalon[®] lettering
- Complete engine packages

Specifications and Details

AF14 / AF16		4.8		5.7		5.85		6.5	
						The section of the se	2		
LOA:	13'9" / 15'10"	LOA:	15'7"	LOA:	18'7"	LOA:	19'4"	LOA:	21'5"
Beam:	5'9" / 6'9"	Beam:	6'11"	Beam:	8'5"	Beam:	8'	Beam:	8'5"
Weight (w/out engine):	315 lbs / 390 lbs	Weight (w/out engine):	685 lbs	Weight (w/out engine):	1,890 lbs	Weight (w/out engine):	1,295 lbs	Weight (w/out engine):	1,365 lbs
Dead rise aft:	N/A	Dead rise aft:	23°	Dead rise aft:	22°	Dead rise aft:	22°	Dead rise aft:	25°
Dead rise forward:	N/A	Dead rise forward:	43°	Dead rise forward:	43°	Dead rise forward:	43°	Dead rise forward:	44°
Tube diameter:	20" / 20"	Tube diameter:	18"	Tube diameter:	20"	Tube diameter:	20"	Tube diameter:	20"
Internal length on deck:	10'2" / 11'6"	Internal length on deck:	11'10"	Internal length on deck:	13'10"	Internal length on deck:	14'9"	Internal length on deck:	16'4"
Internal beam on deck:	2'8" / 3'2"	Internal beam on deck:	4'1"	Internal beam on deck:	4'11"	Internal beam on deck:	5'1"	Internal beam on deck:	5'6"
Draft (w/out engine):	7" / 7"	Draft (w/out engine):	12"	Draft (w/out engine):	14"	Draft (w/out engine):	14"	Draft (w/out engine):	16"
Maximum people:	8 / 10	Maximum people:	6	Maximum people:	10	Maximum people:	10	Maximum people:	12
Max HP:	50 / 60	Max HP:	70	Max HP:	165	Max HP:	135	Max HP:	180
Fuel capacity:	6.6 gal*	Fuel capacity:	6.6 gal*	Fuel capacity:	33 gal	Fuel capacity:	46 gal	Fuel capacity:	60 gal
Tube:	1880 dtx Hypalon®	Tube:	1670 dtx Hypalon®	Tube:	1670 dtx Hypalon®	Tube:	1670 dtx Hypalon®	Tube:	1670 dtx Hypalon®
Chambers:	4+2 / 5+2	Chambers:	5	Chambers:	5	Chambers:	5	Chambers:	5
Pressure relief valves:	4/5	Pressure relief valves:	5	Pressure relief valves:	5	Pressure relief valves:	5	Pressure relief valves:	5

*external tank

*external tank; optional internal



Optional Equipment

Seating

Rescue console

Pod seat(s)

Leaning post upgrade (backrest & footrest)

Full width aft bench seat

Three person bench seat with storage



Rescue Console



Pod seat(s)



Leaning post upgrade (backrest & footrest)

Arches & Tops

Antenna arch

Antenna arch with dive ladder

T-top (not available on 4.8)

T-top courtesy upgrade

Folding bimini (4.8 & 5.85 only)



Antenna arch



Antenna arch with dive ladder



T-top

Accessories

Windscreen

Tow post (fore/aft)

Transom bollards

Engine crash rail

Lifting points

Keel guard

Aluminum beaching shoe

Dive tank storage



Engine crash rail



Tow post



Transom bollards

Tube Options

Reinforced tube at bow

Rubstrake reinforcing

Boarding wear patches

Tube grab handles

Paddle/hook retainers

Custom lettering



Reinforced tube at bow



Boarding wear patches



Tube grab handles

Various tube and hull colors include: Light Grey, Dark Grey, White, Blue, Cream, Black, Red, Yellow, Orange. Electronics, lighting, and navigation packages available.



RIBCRAFT USA, LLC | TEL: 781.639.9065 | FAX: 781.639.9062 | www.ribcraftusa.com | info@ribcraftusa.com