

9.0 Offshore



UNMATCHED PERFORMANCE. HIGH CAPACITY. POWERFUL.



The workhorse of the RIBCRAFT line, the 9.0 is designed specifically for offshore rough water conditions.

A pronounced deep V hull coupled with full length lifting strakes, the 9.0 is designed specifically for rough water conditions that provides for unparalleled handling characteristics. Used by a variety of professionals from military and law enforcement agencies to tour operators and commercial organizations, the 29' RIBCRAFT 9.0 provides generous deck space for people and equipment. With numerous deck configurations available ranging from an open center console to multiple pod seats or a console enclosure, the RIBCRAFT 9.0 accommodates most applications.

9.0 SPECS

LOA:	29'7"	INTERNAL LENGTH ON DECK:	22'10"
BEAM:	10'3"	INTERNAL BEAM ON DECK:	6'10"
WEIGHT (W/OUT ENGINE):	3,820 LBS	DRAFT (W/OUT ENGINE):	22"
DEAD RISE AFT:	20°	MAXIMUM PEOPLE:	20
DEAD RISE FORWARD:	40°	MAX HP:	700
TUBE DIAMETER:	21"		

9.0 STANDARD EQUIPMENT:

- Center console with front bench seat and internal compartment
- Leaning post
- Bow storage locker
- 135 gallon internal fuel tank
- Hydraulic steering with wheel
- 1670 dtx Hypalon® tube with 7 chambers and pressure relief valves
- Stainless steel bow eye
- External lifelines
- Heavy duty rubstrake
- Stainless steel bow cleat
- Stainless steel transom tie down eyes
- Battery with retainer (2) and switch
- Electrical panel
- Navigation lights
- Compass
- Electric bilge pumps (3)
- Molded non-skid deck






9.0 OPTIONAL EQUIPMENT: (PARTIAL LIST)

- Explorer console with operator bolster
- Dual position helmseat with storage
- Windscreen
- Custom console enclosures
- Marine head
- Pod seating with upholstered backrest and grab handle
- Three person bench seat with storage locker
- Molded aft bench seat
- Suspension seating
- Antenna arch
- Antenna arch with integrated dive ladder
- T-top
- Adventure top with integrated dive ladder
- Fore and aft tow posts
- Transom bollards
- Crash rail
- Dive tank storage
- Keel guard
- Aluminum beaching shoe
- Reinforced tube at bow
- Boarding wear patches
- Tube grab handles
- Paddle/hook retainers
- Strobe and safety lights
- Electronics packages
- Fire suppression capabilities
- Complete inboard and outboard engine packages
- USCG Certified Tour & Passenger-for-Hire packages
- Various hull and tube colors

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, the 9.0 can be personalized to the mission.

All specifications, equipment, and options are subject to change without notice.

Specifications and Details

6.8	7.0	7.8	9.0	11.0/12.5
				
LOA: 22'5"	LOA: 24'	LOA: 25'7"	LOA: 29'7"	LOA: 35' 7" / 41'
Beam: 8'8"	Beam: 8'8"	Beam: 8'9"	Beam: 10'3"	Beam: 11' 7" / 12'
Weight (w/out engine): 2,275 lbs	Weight (w/out engine): 2,550 lbs	Weight (w/out engine): 2,670 lbs	Weight (w/out engine): 3,820 lbs	Weight (w/out engine): 7,140 lbs / 8,430 lbs
Dead rise aft: 24°	Dead rise aft: 23°	Dead rise aft: 24°	Dead rise aft: 20°	Dead rise aft: 24° / 22°
Dead rise forward: 45°	Dead rise forward: 45°	Dead rise forward: 45°	Dead rise forward: 40°	Dead rise forward: 43° / 46°
Tube diameter: 20"	Tube diameter: 21"	Tube diameter: 20"	Tube diameter: 21"	Tube diameter: 22"
Internal length on deck: 16'10"	Internal length on deck: 19'3"	Internal length on deck: 20'	Internal length on deck: 22'10"	Internal length on deck: 30' 7"/35' 6"
Internal beam on deck: 5'10"	Internal beam on deck: 5'2"	Internal beam on deck: 5'10"	Internal beam on deck: 6'10"	Internal beam on deck: 8' 6" / 9'
Draft (w/out engine): 18"	Draft (w/out engine): 15"	Draft (w/out engine): 18"	Draft (w/out engine): 22"	Draft: 2' 4" / 2' 6"
Maximum people: 12	Maximum people:	Maximum people: 14	Maximum people: 20	Maximum people: 21 / 37
Max HP: 230	Max HP: 350	Max HP: 300	Max HP: 700	Max HP: 900 / 1275
Fuel capacity: 80 gal	Fuel capacity: 70 gal	Fuel capacity: 100 gal	Fuel capacity: 135 gal	Fuel capacity: 395 gal / 515 gal
Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®
Chambers: 5	Chambers: 7	Chambers: 7	Chambers: 7	Chambers: 9 / 11
Pressure relief valves: 5	Pressure relief valves: 7	Pressure relief valves: 7	Pressure relief valves: 7	Pressure relief valves: 9 / 11

All specs, equipment and options subject to change without notice. | LOA and beam may vary slightly based on inflation pressure of the tube. | Additional dimensions/specs available on request.

Optional Equipment

Seating

Explorer console

Pod seat(s)

Aft molded bench seat

Centerline back to back bench seat

Full width aft bench seat

Suspension seating



Explorer console



Pod seat(s)



Full width aft bench seat

Arches & Tops

Antenna arch

Antenna arch with dive ladder

T-top

T-top courtesy upgrade

Aluminum top upgrade

Adventure top



Antenna arch with dive ladder



T-top



Adventure top

Accessories

Console enclosure

Windscreen

Tow post (fore/aft)

Transom bollards

Engine crash rail

Lifting points

Keel guard / Aluminum beaching shoe

Dive tank storage



Console enclosure



Engine crash rail



Transom bollards

Tube Options

Reinforced tube at bow

Rubstrake reinforcing

Boarding wear patches

Tube grab handles

Paddle/hook retainers

Custom lettering



Reinforced tube at bow



Boarding wear patches



Tube grab handles

Various tube and hull colors include: Light Grey, Dark Grey, White, Blue, Cream, Black, Red, Yellow, Orange. Electronics, lighting, and navigation packages available.

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, all models can be personalized to the mission.