

4.8



AGILE PERFORMER. DEPLOYABLE. STABLE.

At just under 16', the RIBCRAFT 4.8 employs the RIBCRAFT signature deep V hull to offer superior handling and performance for a boat of this size.

Used by government agencies and private industry, the 4.8 incorporates the qualities of exceptional safety, design and reliability. This versatile model offers a solid, low maintenance construction and spacious deck. Easily launched by trailer or hoist, the RIBCRAFT 4.8 is an excellent all purpose safety and response craft. The 4.8 features a solid commercial fiberglass hull, a molded non-skid deck and a heavy duty Hypalon® tube with multiple chambers and pressure relief valves.

4.8 SPECS

LOA:	15'7"	INTERNAL LENGTH ON DECK:	11'10"
BEAM:	6'11"	INTERNAL BEAM ON DECK:	4'1"
WEIGHT (W/OUT ENGINE):	685 LBS	DRAFT (W/OUT ENGINE):	12"
DEAD RISE AFT:	23°	MAXIMUM PEOPLE:	6
DEAD RISE FORWARD:	43°	MAX HP:	70
TUBE DIAMETER:	18"		

4.8 STANDARD EQUIPMENT:

- Single seat console with attached pod seat and upholstered backrest
- Stainless steel console grab rail
- Heavy duty no feedback steering with wheel
- 1670 dtx Hypalon® tube with 5 chambers and pressure relief valves
- External lifelines
- Heavy duty rubstrake
- Stainless steel bow eye
- Anchor locker
- Stainless steel bow cleat
- Stainless steel transom tie down eyes
- Battery with retainer and switch
- Electrical panel
- Navigation lights
- Compass
- Electric bilge pump
- Molded non-skid deck






4.8 OPTIONAL EQUIPMENT: (PARTIAL LIST)

- Additional pod seats with upholstered backrest and grab handle
- Two person bench seat with storage locker
- Antenna arch
- Antenna arch with folding dive ladder
- 16 gallon internal fuel tank
- Stainless steel lifting points
- Keel guard
- Aluminum beaching shoe
- Folding bimini
- Fore and aft tow post
- Transom bollards
- Reinforced tube at bow
- Boarding wear patches
- Tube grab handles
- Paddle/hook retainers
- Custom Hypalon® lettering
- Strobe and safety lights
- Electronics packages
- Hydraulic steering
- Complete engine packages
- Various hull and tube colors

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, the 4.8 can be personalized to the mission.

All specifications, equipment, and options are subject to change without notice.

Specifications and Details

AF14 / AF16	4.8	5.7	5.85	6.5
				
LOA: 13'9" / 15'10"	LOA: 15'7"	LOA: 18'7"	LOA: 19'4"	LOA: 21'5"
Beam: 5'9" / 6'9"	Beam: 6'11"	Beam: 8'5"	Beam: 8'	Beam: 8'5"
Weight (w/out engine): 315 lbs / 390 lbs	Weight (w/out engine): 685 lbs	Weight (w/out engine): 1,890 lbs	Weight (w/out engine): 1,295 lbs	Weight (w/out engine): 1,365 lbs
Dead rise aft: N/A	Dead rise aft: 23°	Dead rise aft: 22°	Dead rise aft: 22°	Dead rise aft: 25°
Dead rise forward: N/A	Dead rise forward: 43°	Dead rise forward: 43°	Dead rise forward: 43°	Dead rise forward: 44°
Tube diameter: 20" / 20"	Tube diameter: 18"	Tube diameter: 20"	Tube diameter: 20"	Tube diameter: 20"
Internal length on deck: 10'2" / 11'6"	Internal length on deck: 11'10"	Internal length on deck: 13'10"	Internal length on deck: 14'9"	Internal length on deck: 16'4"
Internal beam on deck: 2'8" / 3'2"	Internal beam on deck: 4'1"	Internal beam on deck: 4'11"	Internal beam on deck: 5'1"	Internal beam on deck: 5'6"
Draft (w/out engine): 7" / 7"	Draft (w/out engine): 12"	Draft (w/out engine): 14"	Draft (w/out engine): 14"	Draft (w/out engine): 16"
Maximum people: 8 / 10	Maximum people: 6	Maximum people: 10	Maximum people: 10	Maximum people: 12
Max HP: 50 / 60	Max HP: 70	Max HP: 165	Max HP: 135	Max HP: 180
Fuel capacity: 6.6 gal*	Fuel capacity: 6.6 gal*	Fuel capacity: 33 gal	Fuel capacity: 46 gal	Fuel capacity: 60 gal
Tube: 1880 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®
Chambers: 4+2 / 5+2	Chambers: 5	Chambers: 5	Chambers: 5	Chambers: 5
Pressure relief valves: 4 / 5	Pressure relief valves: 5	Pressure relief valves: 5	Pressure relief valves: 5	Pressure relief valves: 5

*external tank

*external tank; optional internal 16 gal tank available

Optional Equipment

Seating

Rescue console

Pod seat(s)

Leaning post upgrade (backrest & footrest)

Full width aft bench seat

Three person bench seat with storage



Rescue Console



Pod seat(s)



Leaning post upgrade
(backrest & footrest)

Arches & Tops

Antenna arch

Antenna arch with dive ladder

T-top (not available on 4.8)

T-top courtesy upgrade

Folding bimini (4.8 & 5.85 only)



Antenna arch



Antenna arch with dive
ladder



T-top

Accessories

Windscreen

Tow post (fore/aft)

Transom bollards

Engine crash rail

Lifting points

Keel guard

Aluminum beaching shoe

Dive tank storage



Engine crash rail



Tow post



Transom bollards

Tube Options

Reinforced tube at bow

Substrake reinforcing

Boarding wear patches

Tube grab handles

Paddle/hook retainers

Custom lettering



Reinforced tube at bow



Boarding wear patches



Tube grab handles

Various tube and hull colors include: Light Grey, Dark Grey, White, Blue, Cream, Black, Red, Yellow, Orange.
Electronics, lighting, and navigation packages available.

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, all models can be personalized to the mission.